


The ultimate rugged touch computer VH-D60G



Product Feature:



Qualcomm CPU
SM 6115
2.0GHz Octa Core



Operating System
Android 11
GMS



Drop Spec.
1.5m



Sealing Standard
IP68



Memory
4GB/64GB



Weight
259g



Scan Engine
Dual ISP
ME5066/SE4770/N6703/CM60



Replaceable Battery
5000mAh
Hot Swap



Retail



Warehouse



Logistics



Field Service

规格参数:

| | |
|---------------------------------|--|
| Model No. | VH-D60G |
| User Environment | |
| Operating Temp. | -20~50°C |
| Storage Temp. | -40~60°C |
| Charging Temp. | 0~45°C |
| Humidity | 5%~95% (non-condensing) |
| Sealing Standard | IP68 |
| Drop Specification | multiple 1.5 m drops to tile over concrete at room temperature without protective boot |
| Tumble Specification | 1000 drops (500 cycles) 0.5m tumbles at room temperature without protective boot |
| ESD | +/-8KV direct discharge, +/-15KV air discharge |
| Physical Characteristics | |
| Dimensions | 164 (L) × 77.2 (W) × 13 (H) mm 6.4 (L) × 3.0 (W) × 0.51 (H) inch |
| Weight | 9.14 oz. / 259 g (Battery included) |
| Display and Panel | <ul style="list-style-type: none"> ▪ 6.0 in. 1080 (W) × 2160 (H) FHD+ industrial-grade IPS display, LED backlight 450nit ▪ Corning® Gorilla® Glass ▪ Capacitive touch panel, Support Water & Gloves Touch <p>Mode</p> |

| | |
|-------------------------------------|---|
| <p>Keys and Buttons</p> | <ul style="list-style-type: none"> ▪ Front key: 3 touch soft keys ▪ Side key: Scan key left and right, volume key up and down, power key and one function key (programmable) |
| <p>Indicators and Notifications</p> | <ul style="list-style-type: none"> ▪ 2*Multi-color LEDs supported (1*green/red LEDs, 1*green/blue LEDs) ▪ Audible tone ▪ Vibration |
| <p>Expansion Slots</p> | <ul style="list-style-type: none"> ▪ One user accessible micro SD Memory slot with SDHC compliance, 512GB ▪ 2*Nano SIM slots ▪ USB 2.0 (type-C) support USB OTG ▪ Support DC in 5V/3A ▪ 4 Pin Bottom connection DCIN, GND, USBDP, USBDM DCIN &GND: Current rating: 3A ▪ 10 Pin Rear connection GPIO1, GND: Trigger key signal DP, DM: USB 2.0 signal TX, RX: UART signal DCIN, GND: Charging port 5V/3A VOUT: 5V/3A out GPIO2: programmable gpio signal |
| <p>Battery</p> | <ul style="list-style-type: none"> ▪ Removable & Rechargeable 3.85V 5000mAh Li-ion Polymer battery pack |

| | |
|---------------------------|---|
| | <ul style="list-style-type: none"> ▪ Warm Swap battery mode up to 5 minutes |
| Power Adapter | <ul style="list-style-type: none"> ▪ 100~240Vac, 50/60Hz Input ▪ 9V/2A 18W QC Fast Charging Output |
| Network Connection | |
| Wireless PAN | Bluetooth 5.1 |
| Wireless LAN | <ul style="list-style-type: none"> ▪ IEEE 802.11 ac/a/b/g/n/ax ready/d/e/h/i/j/k/r/v/w (2.4G/5G Dual band Wi-Fi) ▪ Compliant with WEP, WPA/WPA2-PSK, WAPI, WAPI-PSK ▪ EAP: EAP-TLS, EAP-TTLS, PEAP-MSCHAPv2, PEAP-TLS, PEAP-GTC, PWD, SIM, AKA ▪ Supports 802.11r Fast Roaming |
| Wireless WAN | <ul style="list-style-type: none"> ▪ TDD-LTE (B34/B38/B39/B40/B41) ▪ FDD-LTE (B1/B2/B3/B4/B5/B7/B8/B9/B12/B13/B17/B19/B20/B25/B26/B28A/B28B/B30/B66) ▪ WCDMA (B1/B2/B4/B5/B6/B8/B9/B19) ▪ TD-SCDMA (B34/B39) ▪ CDMA2000 1x EV-DO Rev. A BC0 (800MHz) ▪ CDMA 1x ▪ GSM/EDGE/GPRS (850/900/1800/1900) |
| GPS | GPS, Glonass, Beidou, Galileo |
| Data Capture | |
| Scan Engine | <ul style="list-style-type: none"> ▪ Honeywell: N6703/N6603/HS7 |

| | |
|----------------|---|
| | <ul style="list-style-type: none">▪ Zebra: SE4770/SE4720/SE4710▪ MinDeo: ME5066/ME8600▪ Newland: CM60▪ Front camera : 5M pixel CMOS color camera |
| Camera | <ul style="list-style-type: none">▪ Rear camera : 13M pixels CMOS color camera with PDAF▪ LED flash light with torch |
| NFC (Optional) | High RF output power; ISO15693, ISO14443A/B, MIFARE: Mifare S50, Mifare S70, Mifare UltraLight, Mifare Pro, Mifare Desfire, FeliCa Supported cards |
| Sensor | Light sensor, Proximity sensor, Accelerator sensor, e-Compress, Gyroscope, Fingerprint Sensor (Optional) |

Accessories

| | |
|-------------|--|
| | <ul style="list-style-type: none">▪ Adapter▪ USB Charging Cable (Type C)▪ Spare Battery (Optional) |
| Accessories | <ul style="list-style-type: none">▪ Cradle (1 Terminal) (Optional)▪ Cradle (4 slot for Battery) (Optional)▪ OTG Cable (Optional)▪ Pistol-grip trigger handle (Optional) |